

**A807 LED** Weight: 1.0 lb.







Project Name: Quantity: Fixture Type: **Customer:** 

Material:
RLM shades are constructed of 12 gauge 1100
series spun aluminum. Wall back plate and driver
housing are cast aluminum, some types include a
spun metal cover. All fasteners are stainless steel. Some washers may be galvanized. Inside of shade is reflective white finish for all colors except galvanized paint finish. Screw hardware may not match paint. hardware may not match paint.

Universal voltage 120-277 is standard. 0-10V, TRIAC and ELV dimming to 1% protocols are standard for LED modules. (Refer to Driver Specification section for other specifications.)

## Electrical:

All luminaires are prewired with 0-10V dimming leads. Post Arms and Wall Mounts are also prewired with line voltage & dimming leads.

## Certifications:

Arm mount, stem mount and wall mount are UL Listed for wet locations. LED Module is IP66.

A polyester powder coat high quality finish. Marine grade finish is available.

### Modifications:

Consult factory for custom or modified designs.

### **Buy American:**

This product is assembled in the USA and meets the Buy America(n) government procurement requirements under FAR, DFARS, and DOT regulations. Click here for additional information.

**FINISHES** \*Premium and Marine Grade Finish have additional charges Standard Marine Premium

Catalog Logic				
RLM Light Style Watt	M10W D Source, Distribution tage & nming	40K RTCW CCT Driver Housing	Mounting Accessories	Outside Shade Finish

Catalog Number	1	2	3	4	5	6	7
A807							

1	LIGHT SOURCE & WATTAGES
	AM10W (10W ANP Module COB)
	AM20W (20W ANP Module COB)

2	DISTRIBUTION
	D (Dome Frosted Acrylic Wide Distribution Lens)

3	CCT (COLOR TEMPERATURE)
	<b>27K</b> (2700K)
	<b>30K</b> (3000K)
	<b>35K</b> (3500K)
	<b>40K</b> (4000K)
	50K (5000K) Consult Factory

4	DRIVER HOUSINGS
	Wall Mount Options Choose Arm in Box 5
RTCW	(Driver Housing for Wall only (E-arms); 6 1/2" OD x 5 5/8" H)
SRTCW	(Smooth Driver Housing for Wall only (E-arms); 6" OD x 2 7/8" H)
RTCNCW	(Driver Housing/No Spun Cover for Wall only (E-arms); 5 7/8" OD x 2 5/8" H)
	Stem Mount Options Choose Stem Size in Box 5
ST-RTCC	(Driver Housing for Stem only; 6 1/2" OD x 5 5/8" H)
ST-SRTCC	(Smooth Driver Housing for Stem only; 6" OD x 2 7/8" H)
ST-RTCNCC	(Driver Housing/No Spun Cover for Stem only; 5 7/8" OD x 2 5/8" H)
E	mergency Backup Housing Options Choose EMG Driver in Box 6
ST-DCCEM	(Emergency Ballast Housing for Stem only; 12" OD x 1 1/2" H)
*Drive	r Housing finish will match fixture finish.

5 MOUNTIN	G SOURCES*
Arm M	lounts
E3 E4 E6 E7 E E15 E18	E8 E10 E11 E12 E25 E36
Wall M	lounts
WM54	WM317
Stem M	Mounts
1/2" (13/16" OD) Rigid Stems	3/4" (1" OD) Rigid Stems
2ST6 2ST12 2ST18	3ST6 3ST12 3ST18
2ST24 2ST36 2ST48	3ST24 3ST36 3ST48
2ST60 2ST72 2ST96	3ST60 3ST72 3ST96
*Arm mount, Wall m will match fi	

6 N	OUNTING ACCESSORIES					
EMG-LEDR05	(5W, LED Emergency Driver, Remote Placement up to 30', ANP Module Only, Provided with Flexible Conduit)					
EMG-LEDR7.8	(7.8W, LED Emergency Driver, Remote Placement up to 30', ANP Module Only, Provided with Flexible Conduit)					
EMG-LEDR10.7	(10.7W, LED Emergency Driver, Remote Placement up to 30', ANP Module Only, Provided with Flexible Conduit)					
EMG-LEDR17	(17W, LED Emergency Driver, Remote Placement up to 30', ANP Module Only, Provided with Flexible Conduit)					
GR07 (7	" Wire Grill)**					
PC (B	utton Photo Cell) Remote Only					
SC (S	croll for Arms)**					
SLC (S	loped Ceiling Mount Canopy, 20° Max)**					
SQ (S	quare Back Plate)**					
SWL (A	(Adjustable Locking Swivel)**					
TBK (T	urn Buckle Kit)**					
factory). Fo	Packs are remote mount only (consult or percent lumens in emergency mode, nical Section at <a href="https://www.ANPlighting.com">www.ANPlighting.com</a>					

\*\*Accessory finish will match fixture finish.

Standard Colors	Standard Grade	Marine Grade*	Premium Colors	Premium Grade*	Marine Grade	
Aspen Green	10	10M	High Gloss Black	01	01M	
Cantaloupe	11	11M	Arctic Silver	14	14M	
Lilac	12	12M	Candy Apple Red	64	64M	
Putty	13	13M	Cobalt Blue	65	65M	
Black	41	41M	Caramel	66	66M	
Forest Green	42	42M	Butterscotch	67	67M	
Bright Red	43	43M	Black Silver	68	68M	
White	44	44M	Gunmetal Gray	69	69M	
Bright Blue	45	45M	Mayan Gold	79	NA	
Sunny Yellow	46	46M	Textured Desert Stone	80	80M	
Aqua Green	47	47M	Extreme Chrome	81	81M	
Galvanized	49	NA	Graystone	82	82M	
Navy	50	50M	Oil Rubbed Bronze	83	83M	
Architectural Bronze	51	51M	Carbon Graphite	96	96M	
Patina Verde	52	52M				
Copper Clay	53	53M				
Silver	56	56M				
Black Verde	61	61M				
Painted Chrome	70	70M				
Painted Copper	71	71M				
Textured Black	72	72M				
Matte Black	73	73M				
Textured Architectural Bronze	76	76M				
Textured White	77	77M				
Textured Silver	78	78M				





Project Name:		
Fixture Type:	Quantity:	
Customer:		

PERFORMANCE TABLE - ANP MODULE - INITIAL LUMENS																						
				2700K			3000K				3500K					4000K						
LED CATALOG	WATTS	DISTRIBUTION	INITIAL LUMENS	lm/W	В	U	G	INITIAL LUMENS	lm/W	В	U	G	INITIAL LUMENS	lm/W	В	U	G	INITIAL LUMENS	lm/W	В	U	G
AM10W	10W	TYPE V	847	85	1	0	0	888	89	1	0	0	899	90	1	0	0	910	91	1	0	0
AM20W	20W	TYPE V	1694	85	1	0	0	1777	89	1	0	0	1799	90	1	0	0	1820	91	1	0	0

MODULE SPECIFICATION
CREE XLAMP™ CMU
Typical Efficacy 90 lm/W
• CCT: 2700K, 3000K, 3500K, 4000K
CRI: 90 (min) 92 Typica
3-Step Ellipse
Certifications: UL Recognized, RoHS, ENEC, REACH

Universal Input: 120-277V
Dimming: 0-10V, TRIAC, ELV (Dims to 1%)
Power Factor @ Full Load >90%
• THD @ Full Load <20%
Constant Current Output 50/60Hz
Operating Temperature: -30°C Minimum
• Lifetime: >50,000 hours
Ingress Protection: IP66

**DRIVER SPECIFICATION** 

## **FINISHES**

- A polyester powder coat high quality finish is electro-statically applied and baked at 430° for exceptional durability and color retention. Products undergo an intensive five-step cleansing and pretreatment process for
- Marine grade finish provides superior salt, humidity and UV protection. This coating withstands up to 3,000
  hours of continuous salt spray, comes with a 5-year warranty and is available in either a textured or gloss

## WARRANTY

See www.ANPlighting.com for complete fixture warranty.

LED warranty information

Certifications: UL Recognized, CE, FCC, Energy Star, DLC, CA Title 24

• \*Limited Warranty: A typical year is defined as 4,380 hours of operation.

# **ACCESSORIES**







РС



SLC









**EMG-LED** 

GR07

SQ

SWL

TBK

sc

# **POPULAR ARM MOUNTS**

Dimensions are Projection x Height | CB included with all arms Click here for all Arm Mount styles








**E4** | 29" x 14"













E10 | 55 1/4" x 18"





E8 | 32 1/4" x 12 1/2"

E11 | 38 1/4" x 17 1/4"

E12 | 40 3/8" x 2"

E15 |16 3/8" x 10 1/2"

E18 | 30 3/4" x 21 3/8"

**E25** | 26" x 5 1/4"

E36 | 23 1/4" x 8"

Project Name:	
Fixture Type:	Quantity:
Customer:	

# **POPULAR WALL MOUNTS**

Dimensions are Projection x Height Click here for all Wall Mount styles





WM54 | 23 3/8" x 18"

WM317 | 15" x 12 3/4"

# **DRIVER HOUSINGS**







**RTCNCW** (5 7/8" OD x 2 5/8" H) Wall Only (E-arms)



SRTCW (6" OD x 2 7/8" H) Wall Only (E-arms)



**RTCC** (6 1/2" OD x 5 5/8" H)



**RTCNCC** (5 7/8" OD x 2 5/8" H)



SRTCC (6" OD x 2 7/8" H)

# **FINISHES COLORS**



PREMIUM														
EXTREME CHROME	ARCTIC SILVER	CARBON GRAPHITE	GRAYSTONE	GUNMETAL GRAY	OIL RUBBED BRONZE	BLACK SILVER	HIGH GLOSS BLACK	CANDY APPLE RED	TEXTURED DESERT STONE	BUTTERSCOTCH	MAYAN GOLD	CARAMEL	COBALT BLUE	



