




CB0201



Weight: 28 lbs
Anchor Bolts: 3

Project: _____

Fixture Type: _____ Quantity: _____

Customer: _____

Specifications



Material:
All parts are durable 356 cast aluminum and high strength extruded aluminum.

Shafts are available in 3" and 4" diameter and wall thickness of .125 or .188.

All hardware provided shall be stainless steel or zinc plated steel.

Mounting:
Standard anchor bolts provided are 3/4" x 18" x 3". Bolts, nuts and washers shall be hot dipped galvanized steel.

Bolt pattern diameter is 9".

Access:
Hand access opening and cover are provided in cast base. Hand hole cover is secured by two stainless steel machine screws. (Tamper-proof screws provided upon request). See drawing for position of hand hole.

4 1/2" bottom hole provided for conduit access.

Grounding:
All cast bases are provided with an aluminum grounding lug integrated to inner wall of shaft, 180 degrees to hand hole. Grounding lug is drilled and tapped to accommodate 1/4-20 stainless steel machine screw.

Pole Height:
Maximum pole height is 14 feet.

Finishing:
A polyester powder coat high quality finish is electro-statically applied and baked at 430° for exceptional durability and color retention. Products undergo an intensive five-step cleansing and pretreatment process for maximum paint adhesion.

Marine grade finish provides superior salt, humidity and UV protection. This coating withstands up to 3000 hours of continuous salt spray, comes with a 5-year warranty and is available in either a textured or gloss surface.

Modifications:
Consult factory for custom or modified designs.

Catalog Logic

CB0201

Cast Base

4S14.188

Shaft

GFI20

Accessory

72

Finish

Catalog Number

1

CB0201

2

3

Additional heights and pole diameters may be available. Contact factory for your specific needs.

| 1 Smooth Shaft Catalog No. | 1 Fluted Shaft Catalog No. | Shaft Diameter | Finished Height | Wall Thickness |
|----------------------------|----------------------------|----------------|-----------------|----------------|
| 3S10.125 | 3F10.125 | 3" | 10' | .125 |
| 3S11.125 | - | 3" | 11' | .125 |
| 3S12.125 | - | 3" | 12' | .125 |
| 3S12.188 | - | 3" | 12' | .188 |
| 3S13.188 | - | 3" | 13' | .188 |
| 4S10.125 | - | 4" | 10' | .125 |
| 4S11.125 | - | 4" | 11' | .125 |
| 4S12.125 | - | 4" | 12' | .125 |
| 4S13.125 | - | 4" | 13' | .125 |
| 4S14.125 | - | 4" | 14' | .125 |
| - | 4F10.188 | 4" | 10' | .188 |
| - | 4F11.188 | 4" | 11' | .188 |
| 4S12.188 | 4F12.188 | 4" | 12' | .188 |
| 4S13.188 | 4F13.188 | 4" | 13' | .188 |
| 4S14.188 | 4F14.188 | 4" | 14' | .188 |

| 2 | ACCESSORIES |
|---------|---|
| GFI15 | (15 amp GFCI receptacle outlet) |
| GFI20 | (20 amp GFCI receptacle outlet) |
| GFI-WPU | (20 amp GFCI receptacle with weather proof in-use cover) |
| BAA | (Cast Banner Arm A for 24" wide banner) |
| BAB | (Cast Banner Arm B for 30" wide banner) |
| BAC | (Cast Banner Arm C for 30" wide banner) |
| LR1 | (Cast Ladder Rest 1) |
| LR3 | (Cast Ladder Rest 3) |
| LR4 | (Cast Ladder Rest 4) |
| LR5 | (Cast Ladder Rest 5) |
| SIGN A | (Cast Sign A; 30" x 9", 8 letters/numbers on one line; requires Banner Arm to hang) |
| SIGN B | (Cast Sign B; 31" x 7", 12 letters/numbers on one line; requires Banner Arm to hang) |
| SIGN C | (Cast Sign C; 27" x 11", two rows of 8 letters/numbers on each line, requires Banner Arm to hang) |
| SIGN D | (Cast Sign D; 11" x 6 1/2", 4 letters/numbers on one line) |
| SIGN E | (Cast Sign E; comes with pole clamp, 24 1/2" x 6", 9 letters/numbers on one line) |
| FPH1 | (Flag Pole Holder) |

| 3 FINISHES | | | |
|----------------|--------------------------|----------------|-----------------------------------|
| Standard Grade | Marine Grade | Standard Grade | Marine Grade |
| 40 | NA Raw Unfinished | 53 | 100 Copper Clay |
| 41 | 101 Black | 56 | 109 Silver |
| 42 | 102 Forest Green | 61 | 106 Black Verde |
| 43 | 114 Bright Red | 70 | 118 Painted Chrome |
| 44 | 107 White | 71 | 105 Painted Copper |
| 45 | 112 Bright Blue | 72 | 108 Textured Black |
| 46 | 123 Sunny Yellow | 73 | 125 Matte Black |
| 47 | 120 Aqua Green | 76 | 121 Textured Architectural Bronze |
| 49 | NA Galvanized | 77 | 127 Textured White |
| 50 | 111 Navy | 78 | 124 Textured Silver |
| 51 | 103 Architectural Bronze | 10 | 130 Aspen Green |
| 52 | 104 Patina Verde | 11 | 131 Cantaloupe |
| 12 | 133 Lilac | 13 | 132 Putty |

Consult factory for additional paint charges and availability