

Project: _____

Fixture Type: _____ Quantity: _____

Customer: _____

Specifications



Material:
All parts are durable 356 cast aluminum and high strength extruded aluminum.

Shafts are available in 3", 4", and 5" diameter and wall thickness of .125 or .188.

All hardware provided shall be stainless steel or zinc plated steel.

Mounting:
Standard anchor bolts provided are 3/4" x 18" x 3". Bolts, nuts and washers shall be hot dipped galvanized steel.

Bolt pattern diameter is 12 1/4".

Access
Hand access opening and cover are provided in cast base. Hand hole cover is secured by two stainless steel machine screws. (Tamper-proof screws provided upon request). See drawing for position of hand hole.

8 3/8" bottom hole provided for conduit access.



Grounding
All cast bases are provided with an aluminum grounding lug integrated to inner wall of shaft, 180 degrees to hand hole. Grounding lug is drilled and tapped to accommodate 1/4"-20 stainless steel machine screw.

Pole Height
Maximum pole height is 16 feet.

Finish:
A polyester powder coat high quality finish is electro-statically applied and baked at 430° for exceptional durability and color retention. Products undergo an intensive five-step cleansing and pretreatment process for maximum paint adhesion.

Marine grade finish provides superior salt, humidity and UV protection. This coating withstands up to 3000 hours of continuous salt spray, comes with a 5-year warranty and is available in either a textured or gloss surface.

Modifications:
Consult factory for custom or modified designs.



CB1501

Weight: 34.5 lbs
Anchor Bolts: 4

Catalog Logic						
CB1501	-	5S16.188	-	GFI20	-	72
Cast Base		Shaft		Accessory		Finish

Catalog Number

1

2

3

CB1501

Additional heights and pole diameters may be available. Contact factory for your specific needs.

1 Smooth Shaft Catalog No.	1 Fluted Shaft Catalog No.	Shaft Diameter	Finished Height	Wall Thickness
3S8.125	3F8.125	3"	8'	.125
3S9.125	3F9.125	3"	9'	.125
3S10.125	3F10.125	3"	10'	.125
3S10.188	-	3"	10'	.188
3S11.188	-	3"	11'	.188
3S12.188	-	3"	12'	.188
4S10.125	-	4"	10'	.125
4S11.125	-	4"	11'	.125
4S12.125	-	4"	12'	.125
4S13.125	-	4"	13'	.125
4S14.125	-	4"	14'	.125
-	4F10.188	4"	10'	.188
-	4F11.188	4"	11'	.188
4S12.188	4F12.188	4"	12'	.188
4S13.188	4F13.188	4"	13'	.188
4S14.188	4F14.188	4"	14'	.188
5S12.125	-	5"	12'	.125
5S13.125	-	5"	13'	.125
5S14.125	-	5"	14'	.125
5S15.125	-	5"	15'	.125
5S16.125	-	5"	16'	.125
5S12.188	5F12.188	5"	12'	.188
5S13.188	5F13.188	5"	13'	.188
5S14.188	5F14.188	5"	14'	.188
5S15.188	5F15.188	5"	15'	.188
5S16.188	5F16.188	5"	16'	.188

2	ACCESSORIES	
GFI15	(15 amp GFCI receptacle outlet)	
GFI20	(20 amp GFCI receptacle outlet)	
GFI-WPU	(20 amp GFCI receptacle with weather proof in-use cover)	
BAA	(Cast Banner Arm A for 24" wide banner)	
BAB	(Cast Banner Arm B for 30" wide banner)	
BAC	(Cast Banner Arm C for 30" wide banner)	
LR1	(Cast Ladder Rest 1)	
LR3	(Cast Ladder Rest 3)	
LR4	(Cast Ladder Rest 4)	
LR5	(Cast Ladder Rest 5)	
SIGN A	(Cast Sign A; 30" x 9", 8 letters/numbers on one line; requires Banner Arm to hang)	
SIGN B	(Cast Sign B; 31" x 7", 12 letters/numbers on one line; requires Banner Arm to hang)	
SIGN C	(Cast Sign C; 27" x 11", two rows of 8 letters/numbers on each line, requires Banner Arm to hang)	
SIGN D	(Cast Sign D; 11" x 6 1/2", 4 letters/numbers on one line)	
SIGN E	(Cast Sign E; comes with pole clamp, 24 1/2" x 6", 9 letters/numbers on one line)	
FPH1	(Flag Pole Holder)	
TP	(Tamper Proof Screws)	

Project: _____
 Fixture Type: _____ Quantity: _____
 Customer: _____



3 FINISHES			
Standard Grade	Marine Grade	Standard Grade	Marine Grade
40	NA	Raw Unfinished	53 100 Copper Clay
41	101	Black	56 109 Silver
42	102	Forest Green	61 106 Black Verde
43	114	Bright Red	70 118 Painted Chrome
44	107	White	71 105 Painted Copper
45	112	Bright Blue	72 108 Textured Black
46	123	Sunny Yellow	73 125 Matte Black
47	120	Aqua Green	76 121 Textured Architectural Bronze
49	NA	Galvanized	77 127 Textured White
50	111	Navy	78 124 Textured Silver
51	103	Architectural Bronze	10 130 Aspen Green
52	104	Patina Verde	11 131 Cantaloupe
12	133	Lilac	13 132 Putty

Consult factory for additional paint charges and availability