

Project: \_\_\_\_\_

Fixture Type: \_\_\_\_\_ Quantity: \_\_\_\_\_

Customer: \_\_\_\_\_

## Specifications

**Fitter:**

Fitter is durable 356 cast aluminum.  
All hardware provided shall be stainless steel or zinc plated steel.

**Acorn:**

Acorns available in clear stipple or white stipple with decorative spun aluminum top.

**Fixture Mounting:**

Post Mount: Post Cap with set screws.  
Fits 3" and 4" poles.

**Drivers:**

Universal voltage 122-277V is standard. 0-10V dimming is standard for LED platforms.

**Electrical:**

Approximately 12" of pull wire extends from luminaire. Additional pull wire provided for post mount arms and wall mounts.

**Finish:**

A polyester powder coat high quality finish.  
Marine grade finish is available.

**Modifications:**


Consult factory for custom or modified designs.

**Certifications:**

UL Listed for outdoor, wet location.

**Buy American:**

This product is assembled in the USA and meets the Buy America(n) government procurement requirements under FAR, DFARS, and DOT regulations. [Click here for additional information.](#)

**LF0336  
LED**

Weight: 26 lbs.

EPA: 1.80

## Catalog Logic

LF0336 12 CL CPS30W18 T5 40K - PC - FIN02 - WM2141 - 72

Luminaire  
Series

Cage

Lens

Light Source  
& Wattage

Optic

CCT

Accessories

Finial

Mounting

Finish

## Catalog Number

1

2

3

4

5

6

7

8

9

LF0336

**1** OPTIONAL CAGES

11, 12, 13, 14, 15

21, 22, 23, 24, 25

31, 32, 33, 34, 35

41, 42, 43, 44, 45

**2** LENS

CL (Clear Stipple Polycarbonate)

WH (White Stipple Polycarbonate)

**3** LIGHT SOURCE & WATTAGES

CPS30W18 (30W TIR Performance Platform)

CPS39W18 (39W TIR Performance Platform, CA Title 24)

CPS46W18 (46W TIR Performance Platform)

CPM78W30 (78W TIR Performance Platform)

CPM90W36 (90W TIR Performance Platform)

CPL120W48 (120W TIR Performance Platform)

**4** OPTICS

T2 (Type II)

T3 (Type III)

T4 (Type IV)

T5 (Type V)

**5** COLOR TEMPERATURE (CCT)

27K (2700K)

30K (3000K)

35K (3500K)

40K (4000K)

**6** ACCESSORIES

HSS90 (90° House Side Shield, polished)

HSS120 (120° House Side Shield, polished)

PHSS90 (90° House Side/Uplight Shield, polished)

PHSS120 (120° House Side/Uplight Shield, polished)

\*EMG-LED20HV (High-Low Motion Sensor/Photocell;  
Driver, remote replacement, for use with  
Platforms, 78W or less)

HLMSPC-06 (High-Low Motion Sensor/Photocell;  
15' - 30' Sensor Mounting Height)

HLMSPC-10 (High-Low Motion Sensor/Photocell;  
8' - 15' Sensor Mounting Height)

PC (Button Photo Cell)

SP (Surge Protector, 10kA &amp; 10kV)

TLPC (Twist Lock photo cell, includes  
receptacle & photo cell)

TL5 (5-pin Twist Lock receptacle)

TL7 (7-pin Twist Lock receptacle)

\*For Emergency lumen output data, see  
Resources section at [www.ANPlighting.com](http://www.ANPlighting.com).

**7** OPTIONAL FINIALS

FIN02, FIN04, FIN05, FIN06, FIN10, FIN12, FIN15,

FIN18, FIN28, FIN39, FIN41, FIN42, FIN48, FIN64,

FIN70

**8** MOUNTING SOURCE

Post Mount Arms  
\*See Page 4 for Style/Size

PA5151

PA8711

Wall Mount Arms  
\*See Page 4 for Style/Size

WM2141

WM8581

PA5171

PA8831

WM2211

WM8831

PA5411

WM3351

PA5621

WM4511

PA5651

WM5131

PA6211

WM5161

PA7911

WM5311

PA8031

WM5601

PA8521

WM7411

PA8571

WM8011

Column Mount  
\*See Page 4 for Style/Size

CM Column Mount

**9** FINISHES

\*Premium and Marine Grade Finish have additional charges

| Standard Colors | Standard Grade | Marine Grade* | Standard Colors               | Standard Grade        | Marine Grade*        |
|-----------------|----------------|---------------|-------------------------------|-----------------------|----------------------|
| Aspen Green     | 10             | 10M           | Copper Clay                   | 53                    | 53M                  |
| Cantaloupe      | 11             | 11M           | Silver                        | 56                    | 56M                  |
| Lilac           | 12             | 12M           | Black Verde                   | 61                    | 61M                  |
| Putty           | 13             | 13M           | Painted Chrome                | 70                    | 70M                  |
| Raw Unfinished  | 40             | NA            | Painted Copper                | 71                    | 71M                  |
| Black           | 41             | 41M           | Textured Black                | 72                    | 72M                  |
| Forest Green    | 42             | 42M           | Matte Black                   | 73                    | 73M                  |
| Bright Red      | 43             | 43M           | Textured Architectural Bronze | 76                    | 76M                  |
| White           | 44             | 44M           | Textured White                | 77                    | 77M                  |
| Bright Blue     | 45             | 45M           | Textured Silver               | 78                    | 78M                  |
| Sunny Yellow    | 46             | 46M           | <b>PREMIUM FINISH</b>         | <b>Premium Grade*</b> | <b>Marine Grade*</b> |
| Aqua Green      | 47             | 47M           | Textured Desert               | 80                    | 80M                  |

Project: \_\_\_\_\_  
 Fixture Type: \_\_\_\_\_ Quantity: \_\_\_\_\_  
 Customer: \_\_\_\_\_

## LED PERFORMANCE

## PLATFORM

| LED Wattage | CCT   | Typical Luminous Flux | System Wattage | Typical Efficacy |
|-------------|-------|-----------------------|----------------|------------------|
| 29W         | 2700K | 2670                  | 30w            | 89               |
|             | 3000K | 2670                  | 30w            | 89               |
|             | 3500K | 3209                  | 30w            | 107              |
|             | 4000K | 3465                  | 30w            | 116              |
| 46W         | 2700K | 4004                  | 46w            | 87               |
|             | 3000K | 4004                  | 46w            | 87               |
|             | 3500K | 4814                  | 46w            | 105              |
|             | 4000K | 5197                  | 46w            | 115              |
| 78W         | 2700K | 7041                  | 80w            | 88               |
|             | 3000K | 7041                  | 80w            | 88               |
|             | 3500K | 8464                  | 80w            | 106              |
|             | 4000K | 9138                  | 80w            | 114              |
| 117W        | 2700K | 10561                 | 120w           | 88               |
|             | 3000K | 10561                 | 120w           | 88               |
|             | 3500K | 12696                 | 120w           | 106              |
|             | 4000K | 13707                 | 120w           | 114              |

## PLATFORM SPECIFICATION:

- Efficacy ranges from 87-116 lumens per watt
- Customized lens precisely directs the light
- Operating temperature of -30C to 55C
- Life: L70 is 60,000 hours
- PLATFORM CCT: 2700K, 3000K, 3500K, and 4000K
- CRI: >70
- Parallel circuitry ensures consistent light output in the event of single LED failure

## PLATFORM DRIVER SPECIFICATION:

- Operates at 400mA
- Dimmable down to 10%
- Built in surge protection
- Constant current output 50/60HZ
- Driver Efficiency > 90% power factor above 99%
- 122 – 277V
- 0-10V dimming protocol is standard

## PLATFORM LISTINGS

- Fully compliant with the RoHS Directive
- Certifications: ETL
- Rated IP65 with an optional IP66 rating

## FINISHES

- A polyester powder coat high quality finish is electro-statically applied and baked at 430° for exceptional durability and color retention. Products undergo an intensive five-step cleansing and pretreatment process for maximum paint adhesion. 5-year warranty for aluminum products. 2-year warranty for steel products.
- Marine grade finish provides superior salt, humidity and UV protection. This coating withstands up to 3,000 hours of continuous salt spray and is available in either a textured or gloss surface. 5-year warranty for aluminum products. 2-year warranty for steel products.

## WARRANTY

See [www.ANPlighting.com](http://www.ANPlighting.com) for complete fixture warranty.

## LED warranty information

- 5 year limited warranty\*
- \*Limited Warranty: A typical year is defined as 4,380 hours of operation.

## ACCESSORIES



HSS90 &amp; HSS120



PHSS90 &amp; PHSS120



EMG-LED 20HV



HLMSPC-06 &amp; HLMSPC-10



PC



TLPC



TL5 &amp; TL7

Project: \_\_\_\_\_  
 Fixture Type: \_\_\_\_\_ Quantity: \_\_\_\_\_  
 Customer: \_\_\_\_\_

### CAGES



CAGE 11



CAGE 12



CAGE 13



CAGE 14



CAGE 15



CAGE 21



CAGE 22



CAGE 23



CAGE 24



CAGE 25



CAGE 31



CAGE 32



CAGE 33



CAGE 34



CAGE 35



CAGE 41



CAGE 42



CAGE 43



CAGE 44




CAGE 45

### FINIALS



FIN02



FIN04



FIN05



FIN06



FIN10



FIN12



FIN15




FIN18




FIN28



FIN39



FIN41



FIN42



FIN48



FIN64



FIN70

Project: \_\_\_\_\_  
 Fixture Type: \_\_\_\_\_ Quantity: \_\_\_\_\_  
 Customer: \_\_\_\_\_

## POST MOUNTS - See Post Arm Section on Website for Specification Sheets and additional post arms. Dimensions are Projection x Height



PA5151 / 14 1/4" x 19 3/4"



PA5171 / 15 1/4" x 25 5/8"



PA5411 / 17 7/8" x 25 1/8"



PA5621 / 19" x 26 1/4"



PA5651 / 20" x 26 1/4"



PA6211 / 22 3/4" x 26 1/2"



PA7911 / 20" x 20 5/8"



PA8031 / 20 1/2" x 20 1/4"



PA8521 / 18 1/4" x 14 1/2"



PA8571 / 24" x 47"



PA8711 / 20" x 20 3/8"



PA8831 / 18 7/8" x 18 7/8"

## COLUMN MOUNT




CM / 5 3/4" SQ x 3 1/2" H

## WALL MOUNTS - See Wall Mount Section on Website for Specification Sheets and additional wall mount arms. Dimensions are Projection x Height.



WM2141 / 18" x 12 3/16"



WM2211 / 15 1/2" x 15 7/8"



WM3351 / 14 1/2" x 22"



WM4511 / 17" x 8"



WM5131 / 11" x 16 3/8"



WM5161 / 15 3/4" x 17 3/4"



WM5311 / 10 7/8" x 9 3/4"



WM5601 / 17 7/8" x 14"



WM7411 / 14" x 15 3/4"



WM8011 / 18 1/4" x 16 3/8"



WM8581 / 17 1/8" x 17 1/2"



WM8831 / 17 1/4" x 16 3/8"

## FINISHES COLORS

### STANDARD

