

Project: _____

Fixture Type: _____ Quantity: _____

Customer: _____

Specifications**Fitter:**

Fitter is durable 356 cast aluminum.
All hardware provided shall be stainless steel or zinc plated steel.

Acorn:

Acorns available in clear stipple or white stipple with decorative spun aluminum top.

Fixture Mounting:

Post Mount: Post Cap with set screws.
Fits 3" and 4" poles.

Drivers:

Universal voltage 122-277V is standard. 0-10V dimming is standard for LED platforms.

Electrical:

Approximately 12" of pull wire extends from luminaire. Additional pull wire provided for post mount arms and wall mounts.

Finish:

A polyester powder coat high quality finish.
Marine grade finish is available.

Modifications:

Consult factory for custom or modified designs.

Certifications:

UL Listed for outdoor, wet location.

Buy American:

This product is assembled in the USA and meets the Buy America(n) government procurement requirements under FAR, DFARS, and DOT regulations. [Click here for additional information.](#)

**LF3330
LED**

Weight: 16.5 lbs.

EPA: 1.51

Catalog Logic

LF3330 **12** **CL** **CPS30W18** **T5** **40K** - **PC** - **FIN02** - **WM2141** - **72**

Luminaire
Series

Cage

Lens

Light Source
& Wattage

Optic

CCT

Accessories

Finial

Mounting

Finish

Catalog Number

1

2

3

4

5

6

7

8

9

LF3330**1 OPTIONAL CAGES**

11, 12, 13, 14, 15

21, 22, 23, 24, 25

31, 32, 33, 34, 35

41, 42, 43, 44, 45

2 LENS**CL** (Clear Stipple Polycarbonate)**WH** (White Stipple Polycarbonate)**3 LIGHT SOURCE & WATTAGES****CPS30W18** (30W TIR Performance Platform)**CPS39W18** (39W TIR Performance Platform, CA Title 24)**CPS46W18** (46W TIR Performance Platform)**CPM78W30** (78W TIR Performance Platform)**CPM90W36** (90W TIR Performance Platform)**4 OPTICS****T2** (Type II)**T3** (Type III)**T4** (Type IV)**T5** (Type V)**5 COLOR TEMPERATURE (CCT)****27K** (2700K)**30K** (3000K)**35K** (3500K)**40K** (4000K)**6 ACCESSORIES****HSS90** (90° House Side Shield, polished)**HSS120** (120° House Side Shield, polished)**PHSS90** (90° House Side/Uplight Shield, polished)**PHSS120** (120° House Side/Uplight Shield, polished)

***EMG-LED20HV** (High-Low Motion Sensor/Photocell;
Driver, remote replacement, for use with
Platforms, 78W or less)

HLMSPC-06 (High-Low Motion Sensor/Photocell;
15' - 30' Sensor Mounting Height)

HLMSPC-10 (High-Low Motion Sensor/Photocell;
8' - 15' Sensor Mounting Height)

PC (Button Photo Cell)**SP** (Surge Protector, 10kA & 10kV)

TLPC (Twist Lock photo cell, includes
receptacle & photo cell)

TL5 (5-pin Twist Lock receptacle)**TL7** (7-pin Twist Lock receptacle)

***For Emergency lumen output data, see
Resources section at www.ANPlighting.com.**

7 OPTIONAL FINIALS**FIN02, FIN04, FIN05, FIN06, FIN10, FIN12, FIN15,****FIN18, FIN28, FIN39, FIN41, FIN42, FIN48, FIN64,****FIN70****8 MOUNTING SOURCE**

Post Mount Arms
*See Page 4 for Style/Size

PA5151**PA8711****PA5171****PA8831****PA5411****PA5621****PA5651****PA6211****PA7911****PA8031****PA8521****PA8571**

Wall Mount Arms
*See Page 4 for Style/Size

WM2141**WM8581****WM2211****WM8831****WM3351****WM4511****WM5131****WM5161****WM5311****WM5601****WM7411****WM8011**

Column Mount
*See Page 4 for Style/Size

CM Column Mount**9 FINISHES**

*Premium and Marine Grade Finish have additional charges

Standard Colors	Standard Grade	Marine Grade*	Standard Colors	Standard Grade	Marine Grade*
Aspen Green	10	10M	Copper Clay	53	53M
Cantaloupe	11	11M	Silver	56	56M
Lilac	12	12M	Black Verde	61	61M
Putty	13	13M	Painted Chrome	70	70M
Raw Unfinished	40	NA	Painted Copper	71	71M
Black	41	41M	Textured Black	72	72M
Forest Green	42	42M	Matte Black	73	73M
Bright Red	43	43M	Textured Architectural Bronze	76	76M
White	44	44M	Textured White	77	77M
Bright Blue	45	45M	Textured Silver	78	78M
Sunny Yellow	46	46M	PREMIUM FINISH	Premium Grade*	Marine Grade*
Aqua Green	47	47M	Textured Desert	80	80M

Project: _____
 Fixture Type: _____ Quantity: _____
 Customer: _____

LED PERFORMANCE

PLATFORM

LED Wattage	CCT	Typical Luminous Flux	System Wattage	Typical Efficacy
29W	2700K	2670	30w	89
	3000K	2670	30w	89
	3500K	3209	30w	107
	4000K	3465	30w	116
46W	2700K	4004	46w	87
	3000K	4004	46w	87
	3500K	4814	46w	105
	4000K	5197	46w	115
78W	2700K	7041	80w	88
	3000K	7041	80w	88
	3500K	8464	80w	106
	4000K	9138	80w	114
117W	2700K	10561	120w	88
	3000K	10561	120w	88
	3500K	12696	120w	106
	4000K	13707	120w	114

PLATFORM SPECIFICATION:

- Efficacy ranges from 87-116 lumens per watt
- Customized lens precisely directs the light
- Operating temperature of -30C to 55C
- Life: L70 is 60,000 hours
- PLATFORM CCT: 2700K, 3000K, 3500K, and 4000K
- CRI: >70
- Parallel circuitry ensures consistent light output in the event of single LED failure

PLATFORM DRIVER SPECIFICATION:

- Operates at 400mA
- Dimmable down to 10%
- Built in surge protection
- Constant current output 50/60HZ
- Driver Efficiency > 90% power factor above 99%
- 122 – 277V
- 0-10V dimming protocol is standard

PLATFORM LISTINGS

- Fully compliant with the RoHS Directive
- Certifications: ETL
- Rated IP65 with an optional IP66 rating

FINISHES

- A polyester powder coat high quality finish is electro-statically applied and baked at 430° for exceptional durability and color retention. Products undergo an intensive five-step cleansing and pretreatment process for maximum paint adhesion. 5-year warranty for aluminum products. 2-year warranty for steel products.
- Marine grade finish provides superior salt, humidity and UV protection. This coating withstands up to 3,000 hours of continuous salt spray and is available in either a textured or gloss surface. 5-year warranty for aluminum products. 2-year warranty for steel products.

WARRANTY

See www.ANPlighting.com for complete fixture warranty.

LED warranty information

- 5 year limited warranty*
- *Limited Warranty: A typical year is defined as 4,380 hours of operation.

ACCESSORIES



HSS90 & HSS120



PHSS90 & PHSS120



EMG-LED 20HV



HLMSPC-06 & HLMSPC-10



PC



TLPC



TL5 & TL7

Project: _____
 Fixture Type: _____ Quantity: _____
 Customer: _____

CAGES



CAGE 11



CAGE 12



CAGE 13



CAGE 14



CAGE 15



CAGE 21



CAGE 22



CAGE 23



CAGE 24



CAGE 25



CAGE 31



CAGE 32



CAGE 33



CAGE 34



CAGE 35



CAGE 41



CAGE 42



CAGE 43




CAGE 44




CAGE 45


FINIALS




FIN02




FIN04




FIN05




FIN06




FIN10




FIN12




FIN15




FIN18




FIN28




FIN39



FIN41




FIN42



FIN48



FIN64



FIN70

Project: _____
 Fixture Type: _____ Quantity: _____
 Customer: _____

POST MOUNTS - See Post Arm Section on Website for Specification Sheets and additional post arms. Dimensions are Projection x Height



PA5151 / 14 1/4" x 19 3/4"



PA5171 / 15 1/4" x 25 5/8"



PA5411 / 17 7/8" x 25 1/8"



PA5621 / 19" x 26 1/4"



PA5651 / 20" x 26 1/4"



PA6211 / 22 3/4" x 26 1/2"



PA7911 / 20" x 20 5/8"



PA8031 / 20 1/2" x 20 1/4"



PA8521 / 18 1/4" x 14 1/2"



PA8571 / 24" x 47"



PA8711 / 20" x 20 3/8"



PA8831 / 18 7/8" x 18 7/8"

COLUMN MOUNT




CM / 5 3/4" SQ x 3 1/2" H

WALL MOUNTS - See Wall Mount Section on Website for Specification Sheets and additional wall mount arms. Dimensions are Projection x Height.




WM2141 / 18" x 12 3/16"



WM2211 / 15 1/2" x 15 7/8"



WM3351 / 14 1/2" x 22"



WM4511 / 17" x 8"



WM5131 / 11" x 16 3/8"



WM5161 / 15 3/4" x 17 3/4"



WM5311 / 10 7/8" x 9 3/4"



WM5601 / 17 7/8" x 14"



WM7411 / 14" x 15 3/4"



WM8011 / 18 1/4" x 16 3/8"



WM8581 / 17 1/8" x 17 1/2"



WM8831 / 17 1/4" x 16 3/8"

FINISHES COLORS

STANDARD

