



## Specifications

## Material:

RLM shades are constructed of 12 gauge 1100 series spun aluminum. Wall back plate and driver housing are cast aluminum, some types include a spun metal cover. All fasteners are stainless steel. Some washers may be galvanized. Inside of shade is reflective white finish for all colors except galvanized paint finish. Screw hardware may not match paint.

## Electrical:

Approximately 6" of pull wire extends from luminaire. All luminaires are prewired with 0-10V dimming leads. Post Arms and Wall Mounts are also prewired with line voltage & dimming leads.

## Drivers:

Universal voltage 120-277 is standard. 0-10V, TRIAC and ELV dimming to 1% protocols are standard for LED modules. (Refer to Driver Specification section for other specifications.)

Project Name: \_\_\_\_\_

Fixture Type: \_\_\_\_\_ Quantity: \_\_\_\_\_

Customer: \_\_\_\_\_

## Certifications:

Cord mounts, arm mount, stem mount and wall mount are UL Listed for dry locations.

## Finish:



A polyester powder coat high quality finish. Marine grade finish is available.

## Modifications:

Consult factory for custom or modified designs.

## Buy American:

This product is assembled in the USA and meets the Buy America(n) government procurement requirements under FAR, DFARS, and DOT regulations. [Click here for additional information.](#)



## OSSDF30 LED

Weight: 9.0 lbs.

## Catalog Logic

|                |              |                                 |              |            |                |             |             |                      |
|----------------|--------------|---------------------------------|--------------|------------|----------------|-------------|-------------|----------------------|
| <b>OSSDF30</b> | <b>GY</b>    | <b>AM30W</b>                    | <b>D</b>     | <b>40K</b> | <b>CRD-DCC</b> | <b>BLSF</b> | <b>N/A</b>  | <b>41</b>            |
| RLM Style      | Fabric Shade | Light Source, Wattage & Dimming | Distribution | CCT        | Driver Housing | Mounting    | Accessories | Outside Shade Finish |

## Catalog Number

1

2

3

4

5

6

7

8

## OSSDF30

## 1 FABRIC SHADES

BG (Beige Hard Back Fabric)

BK (Black Hard Back Fabric)

GY (Gray Hard Back Fabric)

CUST (Custom Hard Back Fabric)

## 2 LIGHT SOURCE &amp; WATTAGES

AM10W (10W ANP Module COB)

AM20W (20W ANP Module COB)

AM30W (30W ANP Module COB)

AM40W (40W ANP Module COB)

## 3 DISTRIBUTION

D (Domed Acrylic Wide Distribution Lens)

## 4 CCT (COLOR TEMPERATURE)

27K (2700K)

30K (3000K)

35K (3500K)

40K (4000K)

## 5 DRIVER HOUSINGS

(Driver Housing only Required with Color Cord and/or Emergency Backup Options)

NA No selection is required if Color Cord or Emergency Backup are not chosen

Cord Mount Options  
Choose Cord Style in Box 6

CRD-DCC (Driver Housing for Color Cord only; 7 3/4" x 1 1/2")

SSC-DCC (Driver Housing for SS Cable/Color Cord only; 7 3/4" x 1 1/2")

Emergency Backup Driver Housing Options  
Choose EMG Driver in Box 7

CRD-DCC-EM-BLC (Emergency Ballast Housing for Black Cord only; 12" x 1 1/2")

CRD-DCC-EM-WHC (Emergency Ballast Housing for White Cord only; 12" x 1 1/2")

SSC-DCC-EM-BLC (Stainless steel cable with 6-foot black cord and 12" canopy)

SSC-DCC-EM-WHC (Stainless steel cable with 6-foot white cord and 12" canopy)

SSC-DCC-EM (Emergency Ballast Housing for SS Cable/ Color Cord only; 12" x 1 1/2")

ST-DCC-EM (Emergency Ballast Housing for Stem only; 12" x 1 1/2")

\*Driver Housing finish will match fixture finish.

## 6 MOUNTING SOURCES\*

## Stainless Steel Cable Mounts

SSC-BLC-5W (Stainless steel cable with 6-foot black cord and 5 3/8" canopy)

SSC-WHC-5W (Stainless steel cable with 6-foot white cord and 5 3/8" canopy)

Cord Mounts  
(See page 3 for color cord style)

NA No Selection Required if: CRD-DCC-EM-BLC; CRD-DCC-EM-WHC; SSC-DCC-EM-BLC or SSC-DCC-EM-WHC is chosen in Box 5.

## SJT Cord

BLC-5W (6' Black 5-Wire SJT Cord)

WHC-5W (6' White 5-Wire SJT Cord)

Solid Fabric Colored Cords  
Must Choose DCC Housing in Box 5

BLSF (6' Black)

ORSF (6' Orange)

GYSF (6' Gray)

LGSF (6' Lime Green)

CHSF (6' Chocolate Brown)

KGSF (6' Kelly Green)

WHSF (6' White)

CBSF (6' Cobalt Blue)

CASF (6' Cardinal)

SBSF (6' Sky Blue)

Patterned Fabric Colored Cords  
Must Choose DCC Housing in Box 5

BWHPF (6' Black/White Houndstooth)

MOSPF (6' Magenta/Orange Stripe)

BIHPF (6' Brown/Ivory Houndstooth)

NMTPF (6' Navy Mini Tweed)

GYCPF (6' Gray/Citrus Yellow)

## Glossy Fabric Colored Cords

Must Choose DCC Housing in Box 5

CPGF (6' Copper Penny)

GMGF (6' Gun Metal)

BRGF (6' Bronze)

SSGF (6' Sterling Silver)

GOGF (6' Gold)

## Stem Mounts\*

1/2" (13/16" OD) Rigid Stems

3/4" (1" OD) Rigid Stems

2ST6 2ST12 2ST18

3ST6 3ST12 3ST18

2ST24 2ST36 2ST48

3ST24 3ST36 3ST48

2ST60 2ST72 2ST96

3ST60 3ST72 3ST96

\*Stem finish will match fixture finish.

Project Name: \_\_\_\_\_

Fixture Type: \_\_\_\_\_ Quantity: \_\_\_\_\_

Customer: \_\_\_\_\_

| 7                                                                                                                                                                                   | MOUNTING ACCESSORIES                                                                                       |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------|
| EMG-LED06                                                                                                                                                                           | (6W, LED Emergency Driver, DCEM Placement, ANP Module Only)                                                |
| EMG-LED10                                                                                                                                                                           | (10W, LED Emergency Driver, DCEM Placement, ANP Module Only)                                               |
| EMG-LED16                                                                                                                                                                           | (16W, LED Emergency Driver, DCEM Placement, ANP Module Only)                                               |
| EMG-LED20                                                                                                                                                                           | (20W, LED Emergency Driver, DCEM Placement, ANP Module Only)                                               |
| EMG-LEDR05                                                                                                                                                                          | (5W, LED Emergency Driver, Remote Placement up to 30', ANP Module Only, Provided with Flexible Conduit)    |
| EMG-LEDR7.8                                                                                                                                                                         | (7.8W, LED Emergency Driver, Remote Placement up to 30', ANP Module Only, Provided with Flexible Conduit)  |
| EMG-LEDR10.7                                                                                                                                                                        | (10.7W, LED Emergency Driver, Remote Placement up to 30', ANP Module Only, Provided with Flexible Conduit) |
| EMG-LEDR17                                                                                                                                                                          | (17W, LED Emergency Driver, Remote Placement up to 30', ANP Module Only, Provided with Flexible Conduit)   |
| *Most EM Packs are remote mount only (consult factory). For percent lumens in emergency mode, see Technical Section at <a href="http://www.ANPlighting.com">www.ANPlighting.com</a> |                                                                                                            |
| **Accessory finish will match fixture finish.                                                                                                                                       |                                                                                                            |

| 8                                                              | FINISHES       |               |                       |                |               |
|----------------------------------------------------------------|----------------|---------------|-----------------------|----------------|---------------|
| *Premium and Marine Grade Finish have additional charges       |                |               |                       |                |               |
| Standard Colors                                                | Standard Grade | Marine Grade* | Premium Colors        | Premium Grade* | Marine Grade* |
| Aspen Green                                                    | 10             | 10M           | High Gloss Black      | 01             | 01M           |
| Cantaloupe                                                     | 11             | 11M           | Arctic Silver         | 14             | 14M           |
| Lilac                                                          | 12             | 12M           | Candy Apple Red       | 64             | 64M           |
| Putty                                                          | 13             | 13M           | Cobalt Blue           | 65             | 65M           |
| Black                                                          | 41             | 41M           | Caramel               | 66             | 66M           |
| Forest Green                                                   | 42             | 42M           | Butterscotch          | 67             | 67M           |
| Bright Red                                                     | 43             | 43M           | Black Silver          | 68             | 68M           |
| White                                                          | 44             | 44M           | Gunmetal Gray         | 69             | 69M           |
| Bright Blue                                                    | 45             | 45M           | Mayan Gold            | 79             | NA            |
| Sunny Yellow                                                   | 46             | 46M           | Textured Desert Stone | 80             | 80M           |
| Aqua Green                                                     | 47             | 47M           | Extreme Chrome        | 81             | 81M           |
| Galvanized                                                     | 49             | NA            | Graystone             | 82             | 82M           |
| Navy                                                           | 50             | 50M           | Oil Rubbed Bronze     | 83             | 83M           |
| Textured Architectural Bronze                                  | 51             | 51M           | Carbon Graphite       | 96             | 96M           |
| Consult Factory for additional paint charges and availability. |                |               |                       |                |               |

8

FINISHES

\*Premium and Marine Grade Finish have additional charges

| Standard Colors                                                | Standard Grade | Marine Grade* | Premium Colors | Premium Grade* | Marine Grade* |
|----------------------------------------------------------------|----------------|---------------|----------------|----------------|---------------|
| Patina Verde                                                   | 52             | 52M           |                |                |               |
| Copper Clay                                                    | 53             | 53M           |                |                |               |
| Silver                                                         | 56             | 56M           |                |                |               |
| Black Verde                                                    | 61             | 61M           |                |                |               |
| Painted Chrome                                                 | 70             | 70M           |                |                |               |
| Painted Copper                                                 | 71             | 71M           |                |                |               |
| Textured Black                                                 | 72             | 72M           |                |                |               |
| Matte Black                                                    | 73             | 73M           |                |                |               |
| Textured Architectural                                         | 76             | 76M           |                |                |               |
| Textured White                                                 | 77             | 77M           |                |                |               |
| Textured Silver                                                | 78             | 78M           |                |                |               |
| Consult Factory for additional paint charges and availability. |                |               |                |                |               |

PERFORMANCE TABLE - ANP MODULE - INITIAL LUMENS

|             |       |              | 2700K          |      |   |   |   | 3000K          |      |   |   |   | 3500K          |      |   |   |   | 4000K          |      |   |   |   |
|-------------|-------|--------------|----------------|------|---|---|---|----------------|------|---|---|---|----------------|------|---|---|---|----------------|------|---|---|---|
| LED CATALOG | WATTS | DISTRIBUTION | INITIAL LUMENS | lm/W | B | U | G | INITIAL LUMENS | lm/W | B | U | G | INITIAL LUMENS | lm/W | B | U | G | INITIAL LUMENS | lm/W | B | U | G |
| AM10W       | 10W   | TYPE V       | 847            | 85   | 1 | 0 | 0 | 888            | 89   | 1 | 0 | 0 | 899            | 90   | 1 | 0 | 0 | 910            | 91   | 1 | 0 | 0 |
| AM20W       | 20W   | TYPE V       | 1694           | 85   | 1 | 0 | 0 | 1777           | 89   | 1 | 0 | 0 | 1799           | 90   | 1 | 0 | 0 | 1820           | 91   | 1 | 0 | 0 |
| AM30W       | 30W   | TYPE V       | 2541           | 85   | 1 | 0 | 0 | 2665           | 89   | 1 | 0 | 0 | 2698           | 90   | 1 | 0 | 0 | 2730           | 91   | 1 | 0 | 0 |
| AM40W       | 40W   | TYPE V       | 3388           | 85   | 2 | 0 | 0 | 3554           | 89   | 2 | 0 | 0 | 3597           | 90   | 2 | 0 | 0 | 3640           | 91   | 2 | 0 | 0 |

| MODULE SPECIFICATION                               |
|----------------------------------------------------|
| • CREE XLAMP™ CMU                                  |
| • Typical Efficacy 90 lm/W                         |
| • CCT: 2700K, 3000K, 3500K, 4000K                  |
| • CRI: >90 MIN (92 TYP)                            |
| • 3-Step Ellipse                                   |
| • Certifications: UL Recognized, RoHS, ENEC, REACH |

| DRIVER SPECIFICATION                                       |
|------------------------------------------------------------|
| • Universal Input: 120-277V                                |
| • Dimming: 0-10V, TRIAC, ELV (Dims to 1%)                  |
| • Power Factor @ Full Load >90%                            |
| • THD @ Full Load <20%                                     |
| • Constant Current Output 50/60Hz                          |
| • Operating Temperature: -30°C Minimum                     |
| • Lifetime: >50,000 hours                                  |
| • Ingress Protection: IP66                                 |
| • Certifications: UL Recognized, CE, CA Title 24, FCC, DLC |

| FINISHES                                                                                                                                                                                                                                             |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| • A polyester powder coat high quality finish is electro-statically applied and baked at 430° for exceptional durability and color retention. Products undergo an intensive five-step cleansing and pretreatment process for maximum paint adhesion. |
| • Marine grade finish provides superior salt, humidity and UV protection. This coating withstands up to 3,000 hours of continuous salt spray, comes with a 5-year warranty and is available in either a textured or gloss surface.                   |

| WARRANTY                                                                                        |
|-------------------------------------------------------------------------------------------------|
| See <a href="http://www.ANPlighting.com">www.ANPlighting.com</a> for complete fixture warranty. |
| LED warranty information                                                                        |
| • 5 year limited warranty*                                                                      |
| • *Limited Warranty: A typical year is defined as 4,380 hours of operation.                     |

Project Name: \_\_\_\_\_

Fixture Type: \_\_\_\_\_ Quantity: \_\_\_\_\_

Customer: \_\_\_\_\_

## ACCESSORIES




EMG-LED


## FABRIC COLORS



BG - Beige



BK - Black



GY - Gray

## DRIVER HOUSINGS

DCC  
(7 3/4" x 1 1/2") Cord OnlyDCC  
(7 3/4" x 1 1/2") Cable/Cord OnlyDCCEM  
(12" x 1 1/2") Cord OnlyDCCEM  
(12" x 1 1/2") Cable/Cord OnlyDCCEM  
(12" x 1 1/2")

## SOLID FABRIC COLORED CORDS

All fabric Color Cords are three conductor, 1/4" diameter



GYSF | Gray



CHSF | Chocolate Brown



WHSF | White



CASF | Cardinal



LGSF | Lime Green



KGSF | Kelly Green



CBSF | Cobalt Blue



SBSF | Sky Blue

Project Name: \_\_\_\_\_

Fixture Type: \_\_\_\_\_ Quantity: \_\_\_\_\_

Customer: \_\_\_\_\_

**PATTERNED FABRIC COLORED CORDS**

All fabric Color Cords are three conductor, 1/4" diameter

**BIHPF** | Brown/Ivory Houndstooth**GYCPF** | Gray/Citrus Yellow**MOSPF** | Magenta/Orange Stripe**NMTPF** | Navy Mini Tweed**GLOSSY FABRIC COLORED CORDS**

All fabric Color Cords are three conductor, 1/4" diameter

**SSGF** | Sterling Silver**CPGF** | Copper Penny**BRGF** | Bronze**GOGF** | Gold**FINISHES COLORS****STANDARD****PREMIUM**