



PA215 - POST ARM

Extruded aluminum post arm for pendant fixture.

Catalog Logic

PA215 - 1 - 2 - N/A - 3 - S - 72

Post Arm Style Pendant Post Number of Arms Center Mount Pole Diameter Pole Style Finish

Catalog Number

PA215 - 1 - 2 - N/A - 3 - S - 72

1 Arm Configuration



2 Arm Configuration



1 POST ARM ORIENTATION

1 - Post

3 CENTER MOUNT OPTIONS

N/A

2 NUMBER OF ARMS

1 - One Arm Configuration

2 - Two Arm Configuration

4 POLE DIAMETER

3 - 3 Inch

4 - 4 Inch

5 - 5 Inch

5 POLE STYLE

S - Smooth

F - Fluted

6 FINISHES

Standard Grade	Marine Grade	Standard Grade	Marine Grade
40	NA	Raw Unfinished	53
41	101	Black	56
42	102	Forest Green	61
43	114	Bright Red	70
44	107	White	71
45	112	Bright Blue	72
46	123	Sunny Yellow	73
47	120	Aqua Green	76
49	NA	Galvanized	77
50	111	Navy	78
51	103	Architectural Bronze	10
52	104	Patina Verde	11
12	133	Lilac	13
			132 Putty



Weight: 29.0 lbs
EPA: PA215-1: 0.95
PA215-2: 1.40

Specifications

General:
Due to size or weight, arms mounts may not accommodate all ANP luminaires.

Material:
All parts are durable 356 cast aluminum and high strength extruded aluminum.
All hardware provided shall be stainless steel or zinc plated steel.

Fixture Mounting:
Post Cup mount to tenon.

Post Arm Mounting:
Slip tenon to accommodate 3", 4" and 5" pole. Pole section of arm matches pole diameter and style.

Electrical:
Pull wire provided.

Finish:
A polyester powder coat high quality finish is electro-statically applied and baked at 430° for exceptional durability and color retention. Products undergo an intensive five-step cleansing and pretreatment process for maximum paint adhesion.

Marine grade finish provides superior salt, humidity and UV protection. This coating withstands up to 3000 hours of continuous salt spray, comes with a 5-year warranty and is available in either a textured or gloss surface.

Modifications:
Consult factory for custom or modified designs.