
Quantity:







SINESS	
AA	

Project Name: Fixture Type:

Customer:

Specifications

Material:

RLM shades are constructed of 12 gauge 1100 series spun aluminum. All fasteners are stainless steel. Some washers may be galvanized. Screw hardware may not match paint.

Drivers: Universal voltage 120-277 is standard. 0-10V, TRIAC and ELV dimming to 1% protocols are standard for LED modules. (Refer to Driver Specification section for other specifications.)

Electrical:

Approximately 6" of pull wire extends from luminaire.
All luminaires are prewired with 0-10V dimming leads.

Certifications:

Cord mounts, arm mount, stem mount and wall mount are UL Listed for damp locations. LED Module is IP66.

A polyester powder coat high quality finish. Marine grade finish is available.

Modifications:

Consult factory for custom or modified designs.

Buy American:

This product is assembled in the USA and meets the Buy America(n) government procurement requirements under FAR, DFARS, and DOT regulations. Click here for additional information.

MDM16 LED

Weight: 6.0 lbs.

Catalog Logic MDM16 41 AM20W 27K CRD-DCCEM BLSF EMG-LED16 RLM Style Logic Distribution Wattage & Housing Shade Shade Dimming

Catalog Number	1	2	3	4	5	6	7	8
MDM16								

1.	LIGHT SOURCE & WATTAGES
	AM10W (10W ANP Module COB)
	AM20W (20W ANP Module COB)

2	DISTRIBUTION
	D (Domed Frosted Acrylic Wide Distribution Lens)

3 CCT (COLOR TEMPERATURE)						
	27K (2700K)					
	30K (3000K)					
	35K (3500K)					
	40K (4000K)					

DRIVED HOUSINGS*

4	DRIVER HOUSINGS* (Driver Housing only Required with Color Cord and/or Emergency Backup Options)					
NA		on is required if Color Cord or y Backup are not chosen				
	С	Cord Mount Options noose Cord Style in Box 5				
CR		ver Housing for Color Cord ; 7 3/4" x 1 1/2")				
SS	SSC-DCC (Driver Housing for SS Cable/Color Cord only; 7 3/4" x 1 1/2")					
	Emergency Backup Driver Housing Options Choose EMG Driver in Box 6					
CR	D-DCCEM-BLC	(Emergency Ballast Housing for Black Cord only; 12" x 1 1/2")				
CR	D-DCCEM-WHC	(Emergency Ballast Housing for White Cord only; 12" x1 1/2")				
SS	C-DCCEM-BLC	(Stainless steel cable with 6-foot black cord and 12" canopy)				
SS	C-DCCEM-WHC	(Stainless steel cable with 6-foot white cord and 12" canopy)				
SS	C-DCCEM	(Emergency Ballast Housing for SS Cable/ Color Cord only; 12" x 1 1/2")				
ST-	DCCEM	(Emergency Ballast Housing for Stem only; 12" x 1 1/2")				

*Driver Housing finish will match fixture finish.

5 MOUNTING SOURCES*						
Stainless Steel and Cable Mounts						
SSC-BLC-5W		steel cable with 6-foot and 5 3/8" canopy)				
SSC-WHC-5W		steel cable with 6-foot and 5 3/8" canopy)				
(Se		Mounts color cord style)				
CRD-DC	CEM-WHC;	d if: CRD-DCCEM-BLC; SSC-DCCEM-BLC or s choosen in Box 4.				
	SJT	Cord				
BLC-5W (6' Black	SJT Cord)	WHC-5W (6' White SJT Cord)				
		Colored Cords C Housing in Box 4				
BLSF (6' Black)		KGSF (6' Kelly Green)				
ORSF (6' Orange)		WHSF (6' White)				
GYSF (6' Gray)		CBSF (6' Cobalt Blue)				
LGSF (6' Lime Gre	en)	CASF (6' Cardinal)				
CHSF (6' Chocolai	e Brown)	SBSF (6' Sky Blue)				
		c Colored Cords Housing in Box 4				
BWHPF (6' Black/White Ho	BWHPF (6' Black/White Houndstooth) MOSPF (6' Magenta/Orange Stripe)					
BIHPF (6' Brown/Ivory Ho	undstooth)	NMTPF (6' Navy Mini Tweed)				
GYCPF (6' Gray/C	itrus Yellow)					
		Colored Cords Housing in Box 4				
GMGF (6' Gun Me	tal)	BRGF (6' Bronze)				
SSGF (6' Sterling	Silver)	GOGF (6' Gold)				
CPGF (6' Copper I	Penny)					
Stem Mounts						
1/4" (1/2" OD St 45° Swivel Flat	ems with Canopy)	1/4" (1/2" OD Rigid Stems with Flat Canopy)				
	1STS18 3 1STS48	1STR6 1STR12 1STR18 1STR24 1STR36				
1STS60 1STS72	2 1STS96	1STR48 1STR60 1STR72 1STR96				
*Arm r		nount or Stem finish xture finish.				

6 N	OUNTING ACCESSORIES				
EMG-LED06	(6W, LED Emergency Driver, DCCEM Placement, ANP Module Only)				
EMG-LED10	(10W, LED Emergency Driver, DCCEM Placement, ANP Module Only)				
EMG-LED16	(16W, LED Emergency Driver, DCCEM Placement, ANP Module Only)				
EMG-LED20	(20W, LED Emergency Driver, DCCEM Placement, ANP Module Only)				
EMG-LEDR05	(5W, LED Emergency Driver, Remote Placement up to 30', ANP Module Only, Provided with Flexible Conduit)				
EMG-LEDR7.8	(7.8W, LED Emergency Driver, Remote Placement up to 30', ANP Module Only, Provided with Flexible Conduit)				
EMG-LEDR10.7	(10.7W, LED Emergency Driver, Remote Placement up to 30', ANP Module Only, Provided with Flexible Conduit)				
EMG-LEDR17	(17W, LED Emergency Driver, Remote Placement up to 30', ANP Module Only, Provided with Flexible Conduit)				
factory). Fo	Packs are remote mount only (consult or percent lumens in emergency mode, nical Section at <u>www.ANPlighting.com</u>				
**Acces	**Accessory finish will match fixture finish.				





Project Name:		
Fixture Type:	Quantity:	
Customer:		

FINISHES *Premium and Marine Grade Finish have additional charges						
Standard Colors	Standard Grade	Marine Grade*	Premium Colors	Premium Grade*	Marine Grade*	
Aspen Green	10	10M	High Gloss Black	01	01M	
Cantaloupe	11	11M	Arctic Silver	14	14M	
Lilac	12	12M	Candy Apple Red	64	64M	
Putty	13	13M	Cobalt Blue	65	65M	
Raw Unfinished	40	NA	Caramel	66	66M	
Black	41	41M	Butterscotch	67	67M	
Forest Green	42	42M	Black Silver	68	68M	
Bright Red	43	43M	Gunmetal Gray	69	69M	
White	44	44M	Mayan Gold	79	NA	
Consult Fa	ctory for a	dditiona	I paint charges a	and availab	oility.	

FINISHES *Premium and Marine Grade Finish have additional charges						
Standard Colors	Standard Grade	Marine Grade*	Premium Colors	Premium Grade*	Marine Grade*	
Bright Blue	45	45M	Textured Desert Stone	80	80M	
Sunny Yellow	46	46M	Extreme Chrome	81	81M	
Aqua Green	47	47M	Graystone	82	82M	
Galvanized	49	NA	Oil Rubbed Bronze	83	83M	
Navy	50	50M	Carbon Graphite	96	96M	
Architectural Bronze	51	51M				
Patina Verde	52	52M				
Copper Clay	53	53M				
Silver	56	56M				
Consult Fa	actory for a	dditiona	l paint charges a	nd availab	oility.	

7 8 FINISHES *Premium and Marine Grade Finish have additional charges								
Standard Colors	Standard Grade* Premium Premium Grade* Colors Grade* Grade* Grade*							
Black Verde	61	61M						
Painted Chrome	70	70M						
Painted Copper	71	71M						
Textured Black	72	72M						
Matte Black	73	73M						
Textured Architectural Bronze	76	76M						
Textured White	77	77M						
Textured Silver	78	78M						

PERFORMANCE TABLE - ANP MODULE - INITIAL LUMENS																						
			2700K				3000K				3500K				4000K							
LED CATALOG	WATTS	DISTRIBUTION	INITIAL LUMENS	lm/W	В	U	G	INITIAL LUMENS	lm/W	В	U	G	INITIAL LUMENS	lm/W	В	U	G	INITIAL LUMENS	lm/W	В	U	G
AM10W	10W	TYPE V	847	85	1	0	0	888	89	1	0	0	899	90	1	0	0	910	91	1	0	0
AM20W	20W	TYPE V	1694	85	1	0	0	1777	89	1	0	0	1799	90	1	0	0	1820	91	1	0	0

MODULE SPECIFICATION

- CREE XLAMP™ CMU
- Typical Efficacy 90 lm/W
- CCT: 2700K, 3000K, 3500K, 4000K
- · CRI: 90 (min) 92 Typical
- · 3-Step Ellipse
- Certifications: UL Recognized, RoHS, ENEC, REACH

DRIVER SPECIFICATION

- Universal Input: 120-277V
- Dimming: 0-10V, TRIAC, ELV (Dims to 1%)
- Power Factor @ Full Load >90%
- THD @ Full Load <20%
- · Constant Current Output 50/60Hz
- Operating Temperature: -30°C Minimum
- · Lifetime: >50,000 hours
- Ingress Protection: IP66
- Certifications: UL Recognized, CE, FCC, Energy Star, DLC, CA Title 24

FINISHES

- A polyester powder coat high quality finish is electro-statically applied and baked at 430° for exceptional durability and color retention. Products undergo an intensive five-step cleansing and pretreatment process for maximum paint adhesion
- Marine grade finish provides superior salt, humidity and UV protection. This coating withstands up to 3,000
 hours of continuous salt spray, comes with a 5-year warranty and is available in either a textured or gloss

WARRANTY

See $\underline{www.ANPlighting.com}$ for complete fixture warranty.

LED warranty information

- 5 year limited warranty
- *Limited Warranty: A typical year is defined as 4,380 hours of operation.

DRIVER HOUSINGS















		Fixture Type:	Quantity:							
		Customer:								
SOLID FABRIC COLORED CORDS All fabric Color Cords are three conductor, 1/4" diameter										
GYSF Gray	CHSF Chocolate Brown	WHSF White	CASF Cardinal							
LGSF Lime Green	KGSF Kelly Green	CBSF Cobalt Blue	SBSF Sky Blue							
PATTERNED FABRIC COLORED CORDS All fabric Color Cords are three conductor, 1/4" diameter										
BIHPF Brown/Ivory Houndstooth	GYCPF Gray/Citrus Yellow	MOSPF Magenta/Orange Stripe	NMTPF Navy Mini Tweed							
GLOSSY FABRIC COLORED CORDS All fabric Color Cords are three conductor, 1/4" diameter										
SSGF Sterling Silver	CPGF Copper Penny	BRGF Bronze	GOGF Gold							
EINIGHES COLORS										

Project Name:

FIN	ISHES	COLORS	



