




Specifications

Material:

Constructed of cast aluminum with a sealed glass lens. All hardware is stainless steel. Screw hardware may not match finish. Fixture includes a rubber gasket for weather-tight protection.

Glass:

Choice of clear, frosted or prismatic.

Drivers:

Universal voltage 120-277 is standard. 0-10V, TRIAC and ELV dimming to 1% protocols are standard for LED modules. (Refer to Driver Specification section for other specifications.)

Electrical:

Approximately 6" of pull wire extends from luminaire. All luminaires are prewired with 0-10V dimming leads. Post Arms and Wall Mounts are also prewired with line voltage & dimming leads.

Certifications:

UL Listed for wet locations. LED Module is IP66

Finish:

A polyester powder coat high quality finish. Marine grade finish is available.

Modifications:

Consult factory for custom or modified designs.

Buy American:

This product is assembled in the USA.

VTW100GL LED Weight: 4.0 lbs.

Catalog Logic

VTW100GL	CL	GUPC100		AM20W	D	40K	RTCNC	PC	72
RLM Style	Glass	Guard	Shade Accessories	Light Source, Wattage & Dimming	Distribution	CCT	Driver Housing	Accessories	Outside Shade Finish

Catalog Number

1

2

3

4

5

6

7

8

9

VTW100GL

1	GLASS	
	CL	(Clear Glass)
	FR	(Frosted Glass)
	PR	(Prismatic Glass)
	BLU	(Blue Glass)
	GRN	(Green Glass)
	RED	(Red Glass)

2	GUARD	
	NA	(No Guard)
	GUP 100	(Wire Guard)
	GUPC 100	(Cast Guard)

3	SHADE ACCESSORIES	
	NA	(No Accessory)
	CVTSA 100	(8" Angle Ring)
	CVTSB 100	(8" Step Ring)
	CVTSC 100	(8" Bowl Shade)

4	LIGHT SOURCE & WATTAGES	
	AM10W	(10W ANP Module COB)
	AM20W	(20W ANP Module COB)
	AM30W	(30W ANP Module COB)

5	DISTRIBUTION	
	D	(Dome Frosted Acrylic Wide Distribution Lens)

6	CCT (COLOR TEMPERATURE)	
	27K	(2700K)
	30K	(3000K)
	35K	(3500K)
	40K	(4000K)
	50K	(5000K) Consult Factory

7	DRIVER HOUSINGS	
	Wall Mount Options	
	RTCNCW	(Driver Housing/No Spun Cover for Wall only; 5 7/8" OD x 2 5/8" H)
	*Driver Housing finish will match fixture finish.	

8	MOUNTING ACCESSORIES	
	EMG-LEDR05	(5W, LED Emergency Driver, Remote Placement up to 30', ANP Module Only, Provided with Flexible Conduit)
	EMG-LEDR7.8	(7.8W, LED Emergency Driver, Remote Placement up to 30', ANP Module Only, Provided with Flexible Conduit)
	EMG-LEDR10.7	(10.7W, LED Emergency Driver, Remote Placement up to 30', ANP Module Only, Provided with Flexible Conduit)
	EMG-LEDR17	(17W, LED Emergency Driver, Remote Placement up to 30', ANP Module Only, Provided with Flexible Conduit)
	PC	(Button Photo Cell) Remote Only
	*Most EM Packs are remote mount only (consult factory). For percent lumens in emergency mode, see Technical Section at www.ANPlighting.com	
	**Accessory finish will match fixture finish.	

9	FINISHES					
	*Premium and Marine Grade Finish have additional charges					
Standard Colors	Standard Grade	Marine Grade*	Premium Colors	Premium Grade*	Marine Grade*	
Aspen Green	10	10M	High Gloss Black	01	01M	
Cantaloupe	11	11M	Arctic Silver	14	14M	
Lilac	12	12M	Candy Apple Red	64	64M	
Putty	13	13M	Cobalt Blue	65	65M	
Raw Unfinished	40	NA	Caramel	66	66M	
Black	41	41M	Butterscotch	67	67M	
Forest Green	42	42M	Black Silver	68	68M	
Bright Red	43	43M	Gunmetal Gray	69	69M	
White	44	44M	Mayan Gold	79	NA	
Bright Blue	45	45M	Textured Desert Stone	80	80M	
Sunny Yellow	46	46M	Extreme Chrome	81	81M	
Aqua Green	47	47M	Graystone	82	82M	
Galvanized	49	NA	Oil Rubbed Bronze	83	83M	
Navy	50	50M	Carbon Graphite	96	96M	
Architectural Bronze	51	51M				
Patina Verde	52	52M				
Copper Clay	53	53M				
Silver	56	56M				
Black Verde	61	61M				
Painted Chrome	70	70M				
Painted Copper	71	71M				
Textured Black	72	72M				
Matte Black	73	73M				
Textured Architectural Bronze	76	76M				
Textured White	77	77M				
Textured Silver	78	78M				

Consult Factory for additional paint charges and availability.

Project Name: _____

Fixture Type: _____ Quantity: _____

Customer: _____

PERFORMANCE TABLE - ANP MODULE - INITIAL LUMENS

			2700K					3000K					3500K					4000K				
LED CATALOG	WATTS	DISTRIBUTION	INITIAL LUMENS	lm/W	B	U	G	INITIAL LUMENS	lm/W	B	U	G	INITIAL LUMENS	lm/W	B	U	G	INITIAL LUMENS	lm/W	B	U	G
AM10W	10W	TYPE V	847	85	1	0	0	888	89	1	0	0	899	90	1	0	0	910	91	1	0	0
AM20W	20W	TYPE V	1694	85	1	0	0	1777	89	1	0	0	1799	90	1	0	0	1820	91	1	0	0
AM30W	30W	TYPE V	2541	85	1	0	0	2665	89	1	0	0	2698	90	1	0	0	2730	91	1	0	0

MODULE SPECIFICATION

- CREE XLAMP™ CMU
- Typical Efficacy 90 lm/W
- CCT: 2700K, 3000K, 3500K, 4000K
- CRI: 90 (min) 92 Typical
- 3-Step Ellipse
- Certifications: UL Recognized, RoHS, ENEC, REACH

DRIVER SPECIFICATION

- Universal Input: 120-277V
- Dimming: 0-10V, TRIAC, ELV (Dims to 1%)
- Power Factor @ Full Load >90%
- THD @ Full Load <20%
- Constant Current Output 50/60Hz
- Operating Temperature: -30°C Minimum
- Lifetime: >50,000 hours
- Ingress Protection: IP66
- Certifications: UL Recognized, CE, FCC, Energy Star, DLC, CA Title 24

FINISHES

- A polyester powder coat high quality finish is electro-statically applied and baked at 430° for exceptional durability and color retention. Products undergo an intensive five-step cleansing and pretreatment process for maximum paint adhesion.
- Marine grade finish provides superior salt, humidity and UV protection. This coating withstands up to 3,000 hours of continuous salt spray, comes with a 5-year warranty and is available in either a textured or gloss surface.

WARRANTY

See www.ANPlighting.com for complete fixture warranty.


LED warranty information

- 5 year limited warranty*
- *Limited Warranty: A typical year is defined as 4,380 hours of operation.

ACCESSORIES



CVTSA 100 / 8"



CVTSB 100 / 8"



CVTSC 100 / 8"



EMG-LED



PC

DRIVER HOUSINGS

RTCNCW
(5 7/8" OD x 2 5/8" H) Wall Only

GLASS GUARD

▶ CL = Clear ▶ FR = Frosted ▶ PR = Prismatic

Glass Only
8" H X 4 1/2" W
CL
FR
PR

FINISHES COLORS

STANDARD



PREMIUM

