

Weight: 20.5 lbs.



Specifications

Material:
Durable A356 cast aluminum, 6061 extruded aluminum, and aluminum sheet metal. Hardware is stainless steel or zinc-plated steel. Exposed hardware matches body finish.

Lens:
Clear PMMA Acrylic IES Distribution Lens plus choice of secondary acrylic lens.

Mounting:
3/8" x 10" galvanized steel anchor bolts.

Drivers:
Universal Voltage 120-277V is standard. Dimming: 0-10V to 10%, TRIAC & ELV to 1%. (Refer to Driver Specification section for other specifications.)

Project Name: _____

Bollard Type: _____ Quantity: _____

Customer: _____

Electrical:
A lightning surge protective device is standard (20KA³ Max/10KA³ Nominal). Luminaires are prewired with 0-10V dimming leads.


Finish:
A polyester powder coat high quality finish. Marine grade finish is available.

Modifications:
Consult factory for custom or modified designs.

Certifications:
UL Listed for outdoor, wet location. LED is IP66.

Buy American:
This product is assembled in the USA and meets the Buy America(n) government procurement requirements under FAR, DFARS, and DOT regulations. [Click here for additional information.](#)

Catalog Logic



BL5502 LED

Catalog Number	1	2	3	4	5	6
	BL5502					

1	LENS
CL (Clear Acrylic)	
FR (Frosted Acrylic)	
WH (White Opal Acrylic)	

2	LIGHT SOURCE & WATTAGES
A010LD2 (10W)	
A018LD4 (18W)	
A032LD8 (32W)	

3	OPTICS
T1 (Type I)	
T2 (Type II)	
T3 (Type III)	
T5 (Type V)	

4	CCT (COLOR TEMPERATURE)
27K (2700K)	
30K (3000K)	
35K (3500K)	
40K (4000K)	
AMB (590nm True Amber)	

5	ACCESSORIES
HLMSIN (Integral high-low motion sensor; See page 2 for specifications)	
HSS180-BL5501 (180° House Side Shield)	
IBOLT (Eye Bolt)	
EMG-LEDR05 (5W Emergency Driver)	
EMG-LEDR7.8 (7.8W Emergency Driver)	
EMG-LEDR10.7 (10.7W Emergency Driver)	
EMG-LEDR17 (17W Emergency Driver)	
GFI20 (20 Amp GFCI receptacle outlet)	
GFI-WPU (20 Amp GFCI receptacle w/weather proof in-use cover)	
PC (Dusk-till-dawn Button Photocell)	
Accessory finish will match fixture finish. GFI20 & GFI-WPU standard location is @18" & to the rear of the bollard.	

6 FINISHES					
*Premium and Marine Grade Finish have additional charges					
Standard Colors	Standard Grade	Marine Grade*	Standard Colors	Standard Grade	Marine Grade*
Aspen Green	10	10M	Copper Clay	53	53M
Cantaloupe	11	11M	Silver	56	56M
Lilac	12	12M	Black Verde	61	61M
Putty	13	13M	Painted Chrome	70	70M
Raw Unfinished	40	NA	Painted Copper	71	71M
Black	41	41M	Textured Black	72	72M
Forest Green	42	42M	Matte Black	73	73M
Bright Red	43	43M	Textured Architectural Bronze	76	76M
White	44	44M	Textured White	77	77M
Bright Blue	45	45M	Textured Silver	78	78M
Sunny Yellow	46	46M	PREMIUM FINISH	Premium Grade*	Marine Grade*
Aqua Green	47	47M	Textured Desert	80	80M
Galvanized	49	NA	Graystone	82	82M
Navy	50	50M	Oil Rubbed Bronze	83	83M
Architectural Bronze	51	51M	Carbon Graphite	96	96M
Patina Verde	52	52M			
Consult Factory for additional paint charges and availability.					

Project Name: _____

Fixture Type: _____ Quantity: _____

Customer: _____

PERFORMANCE TABLE - 12 LED ARRAY - CLEAR LENS - DELIVERED LUMENS

LED CATALOG	WATTS	DISTRIBUTION	AMBER				2700K				3000K				3500K				4000K								
			DELIVERED LUMENS	lm/W	B	U	G	DELIVERED LUMENS	lm/W	B	U	G	DELIVERED LUMENS	lm/W	B	U	G	DELIVERED LUMENS	lm/W	B	U	G					
A010LD2	10W	TYPE I	466	47	0	3	1	863	86	1	3	1	933	93	1	3	1	1029	103	1	3	1	1092	109	1	3	1
		TYPE II	465	46	0	3	0	860	86	1	3	1	930	93	1	3	1	1026	103	1	3	1	1088	109	1	3	1
		TYPE III	426	43	0	3	0	849	85	0	3	1	918	92	0	3	1	1013	101	0	3	1	1074	107	0	3	1
		TYPE V	437	44	0	3	0	870	87	1	3	1	941	94	1	3	1	1038	104	3	1	1101	110	1	3	1	
A018LD4	18W	TYPE I	1306	47	1	3	1	1553	86	1	3	1	1679	93	1	3	1	1852	103	1	3	1	1965	109	1	3	1
		TYPE II	837	46	0	3	1	1548	86	1	3	1	1674	93	1	3	1	1847	103	1	3	1	1959	109	1	3	1
		TYPE III	766	43	0	3	1	1528	85	1	3	1	1652	92	1	3	1	1823	101	1	3	1	1933	107	1	3	1
		TYPE V	787	44	1	3	1	1566	87	1	3	1	1693	94	1	3	1	1868	104	1	3	1	1981	110	1	3	1
A032LD8	32W	TYPE I	1490	47	1	3	1	2797	86	2	3	2	3024	93	2	3	2	3337	103	2	3	2	3539	109	2	4	2
		TYPE II	1508	46	1	3	1	2791	86	1	4	1	3018	93	1	4	1	3329	103	1	4	1	3531	109	1	4	1
		TYPE III	1383	43	1	3	1	2757	85	1	3	1	2982	92	1	3	1	3289	101	1	3	1	3489	107	1	4	1
		TYPE V	1419	44	1	3	1	2824	87	2	3	2	3053	94	2	3	2	3368	104	2	3	2	3572	110	2	4	2

LED SPECIFICATION

- PMMA Optical Lens
- 12 High-power LEDs
- Distribution: Type V Round
- Efficacy: 94-120 lm/W
- Distributions: Type I, II, III, V
- CCT: 2700K, 3000K, 3500K, 4000K, 590nm True Amber
- CRI: >90
- Ingress Protection: IP66

DRIVER SPECIFICATION

- Universal Input 120-277V
- Dimming: 0-10V to 10%, TRIAC & ELV to 1%
- Power Factor @ Full Load >90%
- THD @ Full Load <20%
- Constant Current Output 50/60Hz
- Operating Temperature: -30°C Minimum (32W is -10° Minimum)
- Lifetime: >50,000 hours
- Ingress Protection: IP66
- Certifications: UL Recognized, FCC, Energy Star, CA Title 24, RoHS

MOTION SENSOR SPECIFICATION AND FACTORY DEFAULTS

- Sensor Type: Microwave
- 330° Detection Range, Approximately 15' (30' Diameter)
- Dim Levels: High / Low 50%
- Motion Time Delay: 5 min
- For other settings consult factory

Project Name: _____

Fixture Type: _____ Quantity: _____

Customer: _____

FINISHES

- A polyester powder coat high quality finish is electro-statically applied and baked at 430Â° for exceptional durability and color retention. Products undergo an intensive five-step cleansing and pretreatment process for maximum paint adhesion. 5-year warranty for aluminum products. 2-year warranty for steel products.
- Marine grade finish provides superior salt, humidity and UV protection. This coating withstands up to 3,000 hours of continuous salt spray, comes with a 2-year warranty and is available in either a textured or gloss surface.

WARRANTY

See www.ANPlighting.com for complete fixture warranty.

LED warranty information

- 5 year limited warranty*
- ANPlighting.com

ACCESSORIES



IBOLT



EMG-LED



GFI20




GFI-WPU



PHOTOCELL



HLMSIN



HSS180

FINISHES COLORS

STANDARD



PREMIUM

