



Weight: 18.5 lbs.



Specifications

Material:

Durable A356 cast aluminum, 6061 extruded aluminum, and aluminum sheet metal. Hardware is stainless steel or zinc-plated steel. Exposed hardware matches body finish.

Lens:

Choice of Polycarbonate Lens

Mounting:

3/8" x 10" galvanized steel anchor bolts.

Drivers:

Universal Voltage 120-277V is standard. Dimming: 0-10V to 10%, TRIAC & ELV to 1%. (Refer to Driver Specification section for other specifications.)

Project Name: _____

Bollard Type: _____ Quantity: _____

Customer: _____

Electrical:

A lightning surge protective device is standard (20KA³ Max/10KA² Nominal). Luminaires are prewired with 0-10V dimming leads.

Finish:

A polyester powder coat high quality finish. Marine grade finish is available.

Modifications:

Consult factory for custom or modified designs.

Certifications:

UL Listed for outdoor, wet location. LED is IP66.

Buy American:

This product is assembled in the USA and meets the Buy America(n) government procurement requirements under FAR, DFARS, and DOT regulations. [Click here for additional information.](#)

Catalog Logic

BL6221	FR	AM10W	D	40K	-	IBOLT	-	72
Bollard Series	Lens	Light Source & Wattage	Optics	CCT		Accessories		Finish

Catalog Number

1

2

3

4

5

6

BL6221

1 LENS

CL (Clear Polycarbonate)
FR (Frosted Polycarbonate)
WH (White Opal Polycarbonate)

2 LIGHT SOURCE & WATTAGES

AM10W (10W)
AM20W (20W)
AM30W (30W)
AM40W (40W)

3 OPTICS

D (Frosted Domed Acrylic Lens)

4 CCT (COLOR TEMPERATURE)

27K (2700K)
30K (3000K)
35K (3500K)
40K (4000K)

5 ACCESSORIES

HSS180-BL6221 (180° House Side Shield)
IBOLT (Eye Bolt)
EMG-LEDR05 (5W Emergency Driver)
EMG-LEDR7.8 (7.8W Emergency Driver)
EMG-LEDR10.7 (10.7W Emergency Driver)
EMG-LEDR17 (17W Emergency Driver)
GFI20 (20 Amp GFCI receptacle outlet)
GFI-WPU (20 Amp GFCI receptacle w/weather proof in-use cover)
PC (Dusk-till-dawn Button Photocell)
CGFI (Concealed 20 Amp GFCI w/retractable door)
Accessory finish will match fixture finish. GFI20 & GFI-WPU standard location is @18" & to the rear of the bollard.

6 FINISHES

*Premium and Marine Grade Finish have additional charges

Standard Colors	Standard Grade	Marine Grade*	Standard Colors	Standard Grade	Marine Grade*
Aspen Green	10	10M	Copper Clay	53	53M
Cantaloupe	11	11M	Silver	56	56M
Lilac	12	12M	Black Verde	61	61M
Putty	13	13M	Painted Chrome	70	70M
Raw Unfinished	40	NA	Painted Copper	71	71M
Black	41	41M	Textured Black	72	72M
Forest Green	42	42M	Matte Black	73	73M
Bright Red	43	43M	Textured Architectural Bronze	76	76M
White	44	44M	Textured White	77	77M
Bright Blue	45	45M	Textured Silver	78	78M
Sunny Yellow	46	46M	PREMIUM FINISH	Premium Grade*	Marine Grade*
Aqua Green	47	47M	Textured Desert	80	80M
Galvanized	49	NA	Graystone	82	82M
Navy	50	50M	Oil Rubbed Bronze	83	83M
Architectural Bronze	51	51M	Carbon Graphite	96	96M
Patina Verde	52	52M			

Consult Factory for additional paint charges and availability.

Project Name: _____

Fixture Type: _____ Quantity: _____

Customer: _____

LED SPECIFICATION

- COB LED
- Typical Initial Efficacy 120 lm/W
- Distribution: Type V Round
- CCT: 2700K, 3000K, 3500K, 4000K
- CRI: 90 (min) 92 Typical
- 3-Step Ellipse
- Ingress Protection: IP66

DRIVER SPECIFICATION

- Universal Input 120-277V
- Dimming: 0-10V to 10%, TRIAC & ELV to 1%
- Power Factor @ Full Load >90%
- THD @ Full Load <20%
- Constant Current Output 50/60Hz
- Operating Temperature: -30°C Minimum (32W is -10° Minimum)
- Lifetime: >50,000 hours
- Ingress Protection: IP66
- Certifications: UL Recognized, FCC, Energy Star, CA Title 24, RoHS

Project Name: _____

Fixture Type: _____ Quantity: _____

Customer: _____

FINISHES

- A polyester powder coat high quality finish is electro-statically applied and baked at 430Å° for exceptional durability and color retention. Products undergo an intensive five-step cleansing and pretreatment process for maximum paint adhesion. 5-year warranty for aluminum products. 2-year warranty for steel products.
- Marine grade finish provides superior salt, humidity and UV protection. This coating withstands up to 3,000 hours of continuous salt spray, comes with a 2-year warranty and is available in either a textured or gloss surface.

WARRANTYSee www.ANPlighting.com for complete fixture warranty.

LED warranty information

- 5 year limited warranty*
- ANPlighting.com

ACCESSORIES**HSS180****IBOLT****EMG-LED****GFI20****GFI-WPU****PHOTOCELL****CGFI****FINISHES COLORS****STANDARD****PREMIUM**